

Aluminium Test Plugs – 40mm up to 600mm



Product Specification

- Available from 40mm up to 600mm diameter.
- Aluminium plates combine strength with lightness.
- Chemical resistant Seals can be supplied to order.
- “Double Seal” plugs can be supplied to order.
- Steel components are zinc plated to 90 hours salt spray test.
- Carries the Horobin name – quality guaranteed.
- Nominal pipe sizes, minimum and maximum pipe diameters each Plug will fit, maximum test pressure, and weight of Plug are below.
- Plugs have a heat tolerance of Min -30°C to +95°C at a constant temperature.

It is the responsibility of the installer / operator to make sure the maximum allowed back pressure of HOROBIN pipe stoppers are not exceeded.

Please see maximum allowed back pressures in the table below

Part No.	Pipe Size Internal Nominal Diameter		Will Fit Pipes With Internal Diameter		Minimum Insertion into Pipe	Overall length	Contact length	Diameter of waterway	Maximum allowable back pressure	Approx. Weight
	Metric	Imperial	Minimum	Maximum						
71012	40mm	1 1/2"	38mm	50mm	45mm	94mm		1/2"	30 p.s.i.	0.17kg
71022	50mm	2"	49mm	62mm	43mm	90mm		1/2"	30 p.s.i.	0.22kg
71032	65mm	2 1/2"	62mm	77mm	43mm	92mm		1/2"	30 p.s.i.	0.27kg
71042	75mm	3"	73mm	89mm	43mm	94mm		1/2"	20 p.s.i.	0.31kg
71052	90mm	3 1/2"	84mm	103mm	53mm	96mm		1/2"	15 p.s.i.	0.36kg
71062	100mm	4"	94mm	110mm	47mm	94mm		1/2"	10 p.s.i.	0.36kg
71072	114mm	4 1/2"	112mm	130mm	56mm	140mm		1/2"	10 p.s.i.	0.47kg
71082	125mm	5"	125mm	145mm	60mm	95mm		1/2"	10 p.s.i.	0.79kg
71092	150mm	6"	146mm	168mm	48mm	96mm		1/2"	10 p.s.i.	0.70kg
72042	175mm	7"	175mm	200mm	64mm	100mm		1"	7 p.s.i.	1.92kg

72052	200mm	8"	193mm	220mm	64mm	100mm	1"	7 p.s.i	1.59kg
72062	225mm	9"	220mm	240mm	64mm	170mm	1"	7 p.s.i	2.06kg
72072	250mm	10"	245mm	270mm	73mm	178mm	1"	7 p.s.i	2.52kg
72076	275mm	11"	274mm	328mm	100mm	200mm	1"	7 p.s.i	3.45kg
72082	300mm	12"	295mm	325mm	77mm	200mm	1"	7 p.s.i	3.42kg
72092	350mm	14"	350mm	385mm	110mm	215mm	1"	5 p.s.i	6.95kg
72102	375mm	15"	370mm	410mm	110mm	225mm	1"	5 p.s.i	5.35kg
72112	400mm	16"	390mm	435mm	110mm	225mm	1"	5 p.s.i	5.9kg
72131	450mm	18"	445mm	495mm	110mm	225mm	2"	5 p.s.i	8.75kg
72142	500mm	20"	495mm	550mm	145mm	255mm	2"	5 p.s.i	11.3kg
72152	525mm	21"	495mm	550mm	145mm	255mm	2"	3 p.s.i	11.3kg
72162	600mm	24"	595mm	650mm	145mm	255mm	2"	3 p.s.i	15.85kg